

MULTI SPOT



- * Using new generation SMD technology LED.
- * Working position: universal.
- * Opal finish of the lamp cover.
- * Termo conductive material housing of the electronic components: better heath dissipation and more safety for the user.
- * Do not use with dimmer.
- * Wide Beam

Item Characteristics

Code	28560
Lamp Voltage	220-240 V
Nominal Power	5,5 W
Base	GU10
Lamp Current	0,047 A
Nominal Flux	420 LUMEN
Light Tonality	Cool White
Colour temperature	6000 K
Opening beam	100°
Diameter	50 mm
Lenght	54 mm

Performance

Axis cd	170
Irc/Ra	>80
Lifetime	25000 h
Energy Class	A+
kWh/1000h	6
Equivalence with incandescent lamp	61 W

Tech Info

Dimmable	NO
Operating Position	360°
Number of ON-OFF cycles	100000
Power Factor	0,5
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS 2012/19/UE * RAEE 2014/30/UE * Compatibilità Elettromagnetica 2014/35/UE * Bassa Tensione EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3 -2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1:2013) EN 62560 * anno 2013 EN 60968 * anno 2013 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Shipping info

Single pack dimensions L x H x D (mm)	53 x 53 x 72
Item barcode	8011905836047
Pack	10 pz
Inner pack dimensions L x H x D (mm)	280 x 60 x 160
Master barcode	8011905781323
Master pack dimensions L x H x D (mm)	340 x 310 x 370